

INSTALLATION INSTRUCTIONS


MAKE: Chevrolet / GMC **MODEL:** Colorado / Canyon

YEAR: 2015-2022

ENGINE: L4-2.5L / V6-3.6L **FITS:** EC/LB & CC/SB-LB

NOTES: Includes ZR2 & Denali Trims

3" Stainless Steel Cat-Back 49-44099-P (Polished) 49-44099-B (Black) 49-44099 (No Tip)



- **Step 1:** (Read Instructions prior to installation) Secure Vehicle on jack stands (refer to manual for specified jack stand position) remove your stock exhaust up to the catalytic converter from the rear of your truck working your way forward. Take caution not to damage the factory hardware and isolation mounts as they will be reused. It is recommended to not fully tighten the clamps until the entire system has been installed.
- **Step 2:** For faster installation spread the pieces of the exhaust alongside of your vehicle according to the diagram shown.
- **Step 3:** For **CC/SB 128.3**" wheel base install the mid-pipe with the flange using the OE hardware and factory isolation mounts, Then slip on the provided 3" band clamp onto the muffler assembly and install muffler assembly onto mid-pipe and factory isolation mounts. For the **EC/LB 140.5**" wheel base install provided 3" band clamps and 15" extension tube onto mid-pipe assembly with the flange then install muffler assembly onto the extension tube and factory isolation mounts.
- **Step 4:** Utilizing the factory isolation mounts now install over-axle/tailpipe and tip, Align exhaust system and tip to desired position and tighten all band clamps from front to rear.
- **Step 9:** Your installation is now complete. It is recommended to re-tighten all exhaust components after 50-100 miles.

NOTES:

• aFe recommends that the tailpipe be at least 1/2"-1" away from any body panels to avoid heat related body damage. **Tighten and secure.**